Save up to 70% on your home water heating costs!



Smart Water Heating for your home

EcoSpring Water Heaters are the next generation in water heating. Using heat pump technology, naturally occurring thermal energy is harnessed and used to heat the water. This efficient process can reduce your water heating costs by up to 70%



Reduce Power Bill

Save money, with water heating costs reduced by up to 70%.



Renewable Energy

Harnesses naturally occurring thermal energy from the air to heat the water.



4-Year Payback

Typically, the initial investment will be paid back in an average of 4 years (subject to usage).

60					
000	000	000			

Advanced Controls

Offers three operating modes (Economy, Hybrid & E-Heat) to maximise performance and efficiency.



Timely Heating

24 hour timer allows accurate water heating control to take advantage of the higher daytime temperatures & eliminate noise during the night.



Low Operating Noise

At only 49-55dBA* the EcoSpring has a very low noise output, and with an outside installation you'll hardly know it's there. *Measured 1 metre from unit in Heat Pump Mode

Endorsed By All Major Plumbing Merchants

When it comes to EcoSpring, it's a real endorsement when all major plumbing merchants in New Zealand stock our product. They supply product throughout New Zealand and can recommend a qualified plumber for best practice installation.



The Energy Equation

A heat pump is like an energy amplifier. From 1 kW of power input, it can create over 3.6kW of output heat. That's a remarkable performance efficiency of over 300%. Conventional electric storage water heaters can only convert 1 kW of input power into 1 kW of output heat.



1.0kW Electricity Input + 2.60kW Atmospheric Heat Input = 3.60kW Hot Water Output*

Ideal House - 8 homestar rated



We installed an EcoSpring ES300 in our home which was designed to 8 Homestar rating, as well as being a Positive Energy Passive House.


Not only has it contributed to our goal of low energy consumption, but it has also impressed us with its quietness, ease of operation and quick recovery time. We have already recommended it to others and would gladly choose to install one in future projects.

Lee Ann and Murray Durbin, The Ideal House




How EcoSpring Works

EcoSpring Heat Pump Hot Water Cylinders work much like a fridge, but in reverse. They harness the ambient temperature in the air, multiplying this energy to heat the water at a fraction of the operating costs of a traditional hot water cylinder.



Indicative running costs of water heating options*



*Source: http://www.energywise.govt.nz/node/18187 (September 2013)

(Three person household)

EcoSpring Models

The EcoSpring Heat Pump Hot Water Cylinders come in two sizes.

The HP300 is designed for 3+ person household with standard water use and the ES190 is for the smaller household of 1-2 people with standard water use.

Both have the same great technology to save money on heating water. HP300

300 Litre Cylinder



Suitable for 3+ person household with standard water use

Suitable for 1-2 person household with standard water use

Advanced Controls

Economy Mode

The unit utilises the heat pump to heat water. This is the most efficient mode possible, thus allowing the greatest savings.

Hybrid Mode

While the unit uses the heat pump as its primary means to heat the water, the standard electric elements will activate if the ambient air temperature is low.

E-Heat Mode

This mode shuts off the heat pump and only uses the electric elements to heat the water, just like a standard electric water heater. E-Heat mode allows for operation in colder situations (less than -7°C).

Dimensions & Installation

HP300





ES190

Specifications

Model			EcoSpring ES190		EcoSpring HP300		
Mode		Economy	Hybrid	E-Heat		Hybrid	E-Heat
Heating Capacity		1500W	Heat Pump 1500W E-Heat 2150W	2150W	2000W	Heat Pump 2000W E-Heat 3000W	3000W
Rated Input/ Current		529W/ 2.3A	1860W/ 8.1A	2150W/ 9.5A	2000W/ 6A	5000W/ 21.73A	3000W/ 13.04A
Power Supply		220-240V-50Hz			220-240V-50Hz		
Operation Control		Auto/Manual startup, real time control, error alarm, etc			Auto/Manual startup, real time control, error alarm, etc		
Protection		High-pressure protector, overload protector, temp controller and protector, electric leakage protector			High-pressure protector, overload protector, temp controller and protector, electric leakage protector		
Compressor Power		440W			850W		
E-Heater Power		2150W			3000W		
Refrigerant		R134a (0.8kg)			R134a (1.2kg)		
Outlet Water Temp Water Pipeline System Water Side Exchanger		Default 60°C,38°C - 70°C adjustable			Default 55°C, 38°C, - 60°C adjustable		
		Surface heat exchanger			Surface heat exchanger		
	Diameter	DN20			DN20		
Max Pressure		1.0MPa			1.0MPa		
Noise Level*	(dBA)	49			49		
Material Exchanger Air Side Motor Power		Hydrophilic aluminum fin		Hydrophilic aluminum fin			
		Inner groove copper tube			Inner groove copper tube		
		35.5W			68W		
Dimension		568mm x 1580mm			650mm x 1920mm		
Water Tank Capacity		190L			300L		
Net Weight		90kg			145kg		
Cylinder Construction		Enamelled steel			Enamelled steel		
Warranty		3 Year Comprehensive			Storage Tank - 5 Years Compressor - 3 Years		

Install Recommendations

Wall

ES190

600mm

- Install on north facing side of property
- Confirm clearances surrounding the unit Please refer to the diagrams above
- Install on a concrete pad
- · Interior installation Please contact us at 0800 500 210 for requirements

ecospring **service**

Peace of mind

EcoSpring offers a proactive, annual service plan that makes it easy for consumers to maintain their hot water systems.

Annual servicing will not only ensure peak performance, but help extend the life of the system...providing not only peace of mind, but additional value.

Register at: ecospring.co.nz



*Measured 1 metre from unit in Heat Pump Mode



Parex Industries Ltd. | 5 Tolich Place, Henderson 0610. p. (Auckland): 09 836 6566 | p. (nationwide): 0800 200 510 e. info.parex@emerson.com | www.parex.co.nz