

caroma®

Cosmo

Vitreous China
Semi Recessed Vanity Basin

Nominal Size 500mm x 440mm

(Tapware is unavailable)

| | | |
|--------|------------|----|
| CI/SfB | (74.2) | g3 |
| Date | March 2008 | |

Supersedes all previous issues

2.45.1

NEW ZEALAND





Contemporary style doesn't have to mean edges and angles, nor does it have to cost the earth. The Caroma **Cosmo** semi recessed vanity basin is surprisingly economical whilst offering elegant curves and a very modern aesthetic. Combining distinctive style with an efficient design the semi-recessed basin is an intelligent choice. Ideal for narrow counter tops, any bathroom can now have the Cosmo touch.

Tap Holes: The basin is available in one taphole Code No.864015 and three tapholes Code No.864035 options.

Waste Outlet: The basin has been designed for the Caroma Uni-waste outlet suitable for a 40mm trap connection. Coloured plastic flush fitting Uni plug and waste supplied. For applications where a chrome plated brass waste is required there are four suitable Uni-wastes available in the following options — Flush Fitting Plug and Waste Code No.687140, Vandal Resistant Flush Fitting Plug and Waste Code No.687141, Covered Plug and Waste Code No.687142 and Vandal Resistant Covered Plug and Waste Code No.687143.

Bowl Capacity: 4 litres to overflow.

Overflow: Standard with overflow. Designed for maximum tap flow rate of 15 litres/minute.

Fixing: **D.250 Bracket with Tie Hooks** – Supplied. Recommended for domestic and general commercial use. Two D.250 brackets are fixed to the underside of the counter top to secure the tie hooks which anchor the back of the basin to the counter.

The basin must be sealed to the top and front surface of the counter with an acetic cured silicone sealant. **Epoxy type glues must not be used.**

The basin is supplied with a template which must be used for the counter top cut-out.

Important: For granite or marble tops, fix two 20mm thick wooden blocks in the bracket position on the underside of the granite/marble with fast setting two part epoxy. When fully set screw the brackets into position on the wooden blocks. Other suitable fastening systems maybe used.

Colours: White only.

Dimensions: All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

