

MANROSE CLASSIC IN-LINE FAN/LIGHT KITS

EL EXTRACT-A-LITE MODELS

Duct Size	Model No.	Switching Method	Performance	Order Code
100mm	EL100S	Standard	31 l/s, 110m ³ /hr	FAN0420
100mm	EL100T	Timer	31 l/s, 110m ³ /hr	FAN0438
125mm	EL125S	Standard	36 l/s, 130m ³ /hr	FAN2037
125mm	EL125T	Timer	36 l/s, 130m ³ /hr	FAN2038
150mm	EL150S	Standard	89 l/s, 320m ³ /hr	FAN0803
150mm	EL150T	Timer*	89 l/s, 320m ³ /hr	FAN0804

* Includes a 7 minute fixed timer.

- The fan is mounted in the ceiling space, and is therefore able to draw steam directly from source, while at the same time providing spot lighting within your bathroom.
- These fans have been upgraded with ball bearing motors to prolong the life of the motor.
- Electronic Transformer included in the kit to operate the 12V downlight.
- Supported by a 5 year warranty.

ACCESSORIES

Duct Size	Description	Order Code
100mm	EL Diffuser white incl lamp	DCT0360
100mm	EL Diffuser chrome incl lamp	DCT0362
125mm	EL Diffuser white incl lamp	DCT2121
125mm	EL Diffuser chrome incl lamp	DCT2120
150mm	EL Diffuser white incl lamp	DCT1169
150mm	EL Diffuser chrome incl lamp	DCT1171
100mm	Accessory chrome bezel - Extract-a-lite	DCT0366
125mm	Accessory chrome bezel - Extract-a-lite	FAN2076
150mm	Accessory chrome bezel - Extract-a-lite	FAN0827
	12V 35-50W Dichroic lamp with 60° angle beam	FAN0431
	Electronic Transformer 12VAC 50kHz	FAN2101

GENERAL INFORMATION

Models	Diffuser Cut-Out	Interior	Exterior Grille	Duct Type	Length of Duct included
EL100	115mm	White Extract-a-lite incl light	White Eggcrate	Flexible PVC	3m supplied (should not be extended)
EL125	145mm	White Extract-a-lite incl light	White Eggcrate	Flexible PVC	4m supplied (should not be extended)
EL150	165mm	White Extract-a-lite incl light	White Eggcrate	Flexible PVC	5m supplied (you can add up to 12m extra duct)

Please note: Diffuser cut out size is a nominal diameter for a circular cut-out.

Switching Options

1. Standard Model - operates from remote switch (not supplied).
2. Timer Model - Fan operates from a switch, the fan continues to run for a preset time after switching off. The 100 and 125mm models are adjustable between 1-20 minutes, whereas the 150mm models include

a fixed 7 minute timer. Both require: permanent phase and switched phase.

NOTE: All fan flow rates quoted are free air delivery. Performance will be affected by the length of ducting used.



▶ EL150S



▶ 125mm EL Diffusers